



Scapa 207R

Pro-Style Grip Tape

DESCRIPTION

This cohesive grip tape is used primarily by Pro Players. The Pro-Style Grip Tape is a gauze tape that sticks to itself and provides a slightly abrasive feel in a lighter-weight product. Available in 5 colours

APPLICATIONS

Stick handles

PRODUCT BENEFITS

- No adhesive residue upon removal
- Variety of colours available
- Provides a light-weight grip

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesive	Royal Adhesive Latex (20048 Blue, 20044 Black, 20045 Green,	-	C of A
Appearance	20049 Red) Clean-cut edges and core	-	-
Fabric	32/38 (13/11)	Thread Count (Per CM)	-
Length	10 (9.1)	Yards (Metres)	QA - 02
Width	1.5 (38)	Inch (mm)	QA - 03

Version: 18 Generated Date: 26 November 2025 Page: 1 of 2

www.renfrewprotape.com Product Code: 207R

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

• Colours: Red, Blue, White, Black and Green

RECOMMENDATIONS

Application to Surface:

Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure.

Recommended application temperature to achieve best results is 65F (18°C) or above. Proper bonding may not occur unless adhesive and surface materials are both at 65F (18°C) or above.

NOTF:

- 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminates such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
- 2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end

Version: 18 Generated Date: 26 November 2025 Page: 2 of 2

www.renfrewprotape.com Product Code: 207R