RENFREW PRO™
Hockey Tape

Technical DATA

RENFREW HOCKEY TAPE 108R Coloured

Polyflex Coloured Shin Pad Tape

DESCRIPTION

Our Polyflex Coloured Shin Pad tape is formulated to provide sufficient elasticity and memory to hold shin pads and other sports equipment securely in place. It allows players to skate comfortably and confidently throughout their game. This premium shin pad tape comes in 8 different colours and is also available in clear.

APPLICATIONS

- Shin pads

PRODUCT BENEFITS

- Stretchable with memory
- Waterproof polyethylene
- Enhances support
- Hand tearable
- Moisture resistant

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesive Thickness (Synthetic Rubber)	2.5 (.064mm)	Mils (mm)	-
Backing Adhesion (PSTC 101 Mod.) Initial to Backing Substrate (20 in @RT)	35 (9.6)	Oz/Inch (N/25mm)	-
Elongation	80	%	-
Peel Adhesion (PSTC 1 Mod./180°) Initial to S.S.(20 min. @ RT)	60 (16)	Oz/Inch (N/25mm)	-
Tensile Strength	18 (79)	lbs. / inch (N/25mm)	ASTM D 1000
Total Thickness (excluding liner)	7.0 (.178)	Mils (mm)	-

STANDARD PRESENTATIONS

- Colours: Red, Orange, Yellow, Green, Royal Blue, White, Black

RECOMMENDATIONS

Application to Surface: Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

NOTE: 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminates such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.

2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.