



PROBLADE ™ 104R Custom

Pro-Blade™ Custom Patterned Cloth Tape

DESCRIPTION

Our made to order Pro-Blade™ Custom Patterned Cloth Tape is the same great quality as our Pro-Blade™ Stick Tape. Specially designed for today's composite hockey sticks, these tapes incorporate an advanced adhesive formulation applied to a polyester/cotton cloth base, resulting in a more substantial cloth tape with increased wear characteristics. Create your very own custom colour, patterns or logo on this premium cloth stick tape. Contact us to order your custom pattern or colour.

MINIMUM ORDER REQUIREMENTS

Our minimum order to create custom tapes is 15,000 rolls of 24mm x 18M Tape. If you require additional information please contact us.

APPLICATIONS

Stick handles and blades

PRODUCT BENEFITS

- Protects stick blade from abrasion
- Poly/cotton improves durability on one-piece (composite) hockey sticks
- Custom colours and patterns / logos

Version: 25

Generated Date: 08 December 2025

www.renfrewprotape.com Product Code: 104R Custom

Page: 1 of 2

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	10.0 (.254)	Mils (mm)	REN TM 20
Adhesion to Steel	28 (7.7)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Adhesion to Backing	20 (5.5)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Tensile Strength	35 (155.72)	lbs. / inch (N/25mm)	ASTM D 1000

STANDARD PRESENTATIONS

• Colours: Custom Colours, Patterns / Logos

RECOMMENDATIONS

Application to Surface: Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

NOTF:

- 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminates such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
- 2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.

Version: 25 Generated Date: 08 December 2025 Page: 2 of 2

www.renfrewprotape.com Product Code: 104R Custom