



## RENFREW ™ 206R

# StretchRap Grip Tape

### **DESCRIPTION**

This cohesive tape is instrumental for creating custom grips on hockey sticks and other sport equipment handles. The StretchRap Grip Tape is a flexible tape that sticks to itself, is easily torn by hand, provides the exact feel and comfort players prefer and leaves no adhesive residue upon removal. It is available in a range of 11 colours.

### **APPLICATIONS**

Stick handles

## **PRODUCT BENEFITS**

- No adhesive residue upon removal
- Variety of colours available
- Stretchable, allowing for ease in application

## **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Unit	Test Method
Breaking Load (1 1/2" wide)	400	(N/10 cm)	-
Total Length	6 (5.5)	Yards (m)	-
Unwind Force	7.0	(N/10 cm)	-
Weight	260	g/m²	-
Width Tolerance	+/- 1/16" (+/- 1.6)	Inch (mm)	-

## STANDARD PRESENTATIONS

• Colours: Red, Blue, White, Black, Green, Yellow, Orange, Purple, Light Blue, Pink, Lime Green

Version: 19 Generated Date: 07 December 2025 Page: 1 of 2

www.renfrewprotape.com Product Code: 206R

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

#### RECOMMENDATIONS

## Application to Surface:

Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

NOTE: 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminates such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.

2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.

Version: 19 Generated Date: 07 December 2025 Page: 2 of 2

www.renfrewprotape.com Product Code: 206R