



RENPRO 288

RENFREW PRO™ AT Tape

DESCRIPTION

Renfrew Pro™ AT Professional Athletic Tape is specially formulated to meet the demands of amateur and professional athletes. This tape delivers top performance under intense conditions, providing support and helping to restrict motion in muscles and joints. Use AT Tape in conjunction with Renfrew Pro™ 106 Foam Under Wrap to provide a custom applied stabilization while maintaining complete comfort.

APPLICATIONS

- Provides support and conformity to help protect joints from sprains and injury
- Assist in prevention and healing of sports related injuries

PRODUCT BENEFITS

- Helps to prevent injury and support existing injuries
- 100% cotton cloth
- Strong zinc oxide based, single coated adhesive
- Easy to tear by hand
- Vanilla-scented adhesive
- Resists failure caused by moisture
- Perfect for wrists and ankles

TECHNICAL PROPERTIES

| Technical Property | Nominal Value | Unit | Test Method |
|---------------------|---------------|-------------------------|----------------|
| Total Thickness | 10.5 (2.9) | Oz/Inch (N/25mm) | REN TM 20 |
| Adhesion to Steel | 25 (6.95) | Oz/Inch (N/25mm) | PSTC - 101 Mod |
| Adhesion to Backing | 12 (3.3) | Oz/Inch (N/25mm) | PSTC - 101 Mod |
| Tensile Strength | 30 (133.5mm) | lbs. / inch (N/25mm) | ASTM D 1000 |

STANDARD PRESENTATIONS

- Branding: RENFREW PRO AT
- Colours: White
- Core Diameter: 1 Inch
- Core: RENFREW PRO AT Blue
- Packaging: RENFREW PRO AT Blue/White Carton

RECOMMENDATIONS

Application:

RENFREW PRO AT tape may be used in conjunction with other RENFREW PRO Athletics products to provide a custom applied stabilization while maintaining complete comfort to the athlete. In particular, RENFREW PRO Athletics recommends pre-wrapping any area to be taped with our foam underwrap tape for maximum comfort.

RENFREW PRO Athletic tapes should only be applied by trained professionals. Incorrect wrapping may not provide the support needed by the athlete, and if applied too tight, may restrict circulation.

NOTE: Shelf life is one year from date of shipment, when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.