RENFREW PRO™
Hockey Tape

Technical DATA

PROBLADE ™ 503XT

Pro-Blade™ XT Black Cloth Tape

DESCRIPTION

Specially designed for today's composite hockey sticks, Pro-Blade XT™ Black Cloth Tape from Renfrew Pro™ incorporates an advanced adhesive formulation applied to a polyester/cotton cloth base, resulting in a more substantial cloth tape with increased wear characteristics. Pro-Blade™ XT features extra adhesive to last even longer on your stick and provide better grip.

Also available in our Renfrew Pro™ Season Tape Pack with 20 rolls of black Pro-Blade™ Cloth Tape, or our combo pack that includes 6 white and 4 black Pro-Blade™ Cloth Tapes and 10 Polyflex®. Clear Shin Pad Tape rolls.

APPLICATIONS

- Stick handles and blades

PRODUCT BENEFITS

- Protects stick from abrasion
- Helps with puck control
- Moisture resistant
- Improves grip on handle

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	10.5 (.254)	Mils (mm)	REN TM 20
Adhesion to Steel	35 (9.6)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Adhesion to Backing	23 (6.3)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Tensile Strength	45 (200.2)	lbs. / inch (N/25mm)	ASTM D 1000

STANDARD PRESENTATIONS

- Colours: Black

RECOMMENDATIONS

Application to Surface:
Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65F (18°C) or above. Proper bonding may not occur unless adhesive and surface materials are both at 65°F (18°C) or above.

NOTE:
1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminates such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.

2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.