

RENFREW™ M002-SK

Traction Mat Starter Kit

DESCRIPTION

Designed to be an all in one traction solution, the kit is available in two sizes, and includes an athletic traction mat and a base. When the mat is exhausted, the base is designed to be reused with our M002-SP replacement mats.

APPLICATIONS

- Indoor sports where shoe traction is critical
- Use for basketball, volleyball, badminton, tennis, wrestling, table tennis, handball, and indoor fitness

PRODUCT BENEFITS

- Improves traction for athletic footwear on indoor athletic surfaces
- Removes dirt and debris from soles of athletic footwear

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Peel Adhesion (PSTC 101 Mod./180°) Initial to SS (20 min @ RT) Exposed *	9 (2.4)	Oz/Inch (N/25mm)	-
Backing Layer Adhesive Strength (PSTC 101 Mod./180° (floor mounting) (20 min. @ RT)	22 (6.0)	Oz/Inch (N/25mm)	-
Tensile Strength - Longitudinal	3439	PSI	-
Elongation	434	%	-

STANDARD PRESENTATIONS

- Standard Dimensions: 18 inches by 19 inches or 28 inches by 29 inches
- Number of layers: 40
- Colours: Clear mat with a White mat base

RECOMMENDATIONS

Application to Primary Surface: Apply the adhesive side to the mat base. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

NOTE:

- 1) When applying pressure sensitive adhesive films to any surface, be sure that the surface is dry, free from oil or other surface contaminants such as dirt, dust, or release agents.
- 2) Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C) The adhesive layer of the mat becomes slippery when wet.
- 3) The bottom mounting film of the mat is designed for mounting to flooring surfaces but painted surfaces with poor paint adhesion or in areas where the paint adhesion has become compromised, may upon removal, remove paint from the floor surface.