



PROBLADE ™ 101R Split Tape

PRO-BLADE™ SPLIT WHITE CLOTH TAPE

DESCRIPTION

Specially designed for today's composite hockey sticks, Pro-Blade™ Split White Cloth Tape from Renfrew Pro™ incorporates an advanced adhesive formulation applied to a polyester/cotton cloth base, resulting in a more substantial cloth tape with increased wear characteristics. This tape has been split into two widths, offering flexibility in creating a custom and functional grip on the handle of your hockey stick. The wider side can be used for the handle or blade and the narrow side can be twisted or layered to customize your grip.

APPLICATIONS

· Stick handles and blades

PRODUCT BENEFITS

- 2 sizes allow for the creation of custom grip on hockey sticks or other sports handles
- Moisture Resistant
- Helps with puck control
- Protects stick from abrasion

TECHNICAL PROPERTIES

www.renfrewprotape.com

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	10.5 (.266)	Mils (mm)	REN TM 20
Adhesion to Steel	32 (8.8)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Adhesion to Backing	20 (5.5)	Oz/Inch (N/25mm)	PSTC - 101 Mod
Tensile Strength	36 (160)	lbs. / inch (N/25mm)	ASTM D 1000

Version: 7 Generated Date: 07 December 2025

Page: 1 of 2

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

Product Code: 101R Split Tape

STANDARD PRESENTATIONS

• Colours: White

RECOMMENDATIONS

Application to Surface: Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

NOTE:

- 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminates such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
- 2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.

Version: 7 Generated Date: 07 December 2025 Page: 2 of 2

www.renfrewprotape.com Product Code: 101R Split Tape